



HX9510C Polyester Fabric Tape

Application: HX9510C is especially suitable for the wrapping of wire harness. You will obtain a smooth and durable flexible cable harness with overlapping bandaging as with spiral bandaging. Meet VOC requirement

Technical Data:

Properties	Dimension	Values	Test Method
Thickness	mm	0.28	ASTM D1000
Adhesion Strength	N/cm	2.5	ASTM D1000
Tensile Strength	N/cm	60	ASTM D1000
Elongation	%	10	ASTM D1000
Temperature Range	°C	-40/105	LV-312
Unwinding forc	N/mm	2~5	ASTM D1000

Properties

- Colour : Black
- Structure: high quality viscose fabric tape in combination a strong synthetic rubber—based adhesive.
- Advantages:
 - high adhesive force
 - tearable by hand
 - suitable for machine and manual processing
 - free of critical substances
 - flexible and supple
- Shelf life: 12months is the original package at 23°C and 65% relative humidity.

Standard Size:

- Standard length: 20, 25 (m)
- Standard Width: 9, 15, 19, 25, 30, 38, 50, 75 (mm)
- Standard ID of core: 32, 38(mm)

Important Notice to Purchaser: All statements, information and recommendations contained herein are based on tests we believe to be reliable, before using, users shall determine the suitability of the product for their intended uses.